ADDENDUM NO. 1

COUNTY OF KAUA'I DEPARTMENT OF WATER

INVITATION FOR BIDS

GS-2021-03 (2nd Solicitation)

FOR THE
FURNISHING AND DELIVERY
OF

ONE (1) COMPACT LOADER WITH ACCESSORIES

NOTICE TO PROSPECTIVE PROPOSERS

This addendum is hereby made a part of the INVITATION FOR BIDS and shall govern the work, taking precedence over previously issued plans and specifications governing the items mentioned for the subject project; and it shall amend the said contract documents in the following respects:

ADDENDUM NO. 1

The attached revised SPECIFICATIONS shall replace the original Specifications for One (1) Compact Loader with Accessories and be used for submitting this bid. Revisions are highlighted in the specifications.

Bid due date remains the same of Friday, February 5, 2021 by 2pm.

End of Addendum No. 1

If there are any questions, please contact Mr. Val Reyna at (808) 245-5434 or by email at vreyna@kauaiwater.org.



Marites Yano Designated Chief Procurement Officer January 28, 2021

ACKNOWLEDGEMENT OF RECEIPT OF ADDENDUM NO. 1

Receipt Acknowledged:				
Organization	Received by			
Date	Title			

(Please sign and return this acknowledgement.)



SPECIFICATIONS – ITEM NO. 1

ONE (1) COMPACT TRACK LOADER

THE MINIMUM SPECIFICATIONS SHALL NOT BE LESS THAN:

<u></u>	HE MINIMOM SPECIFICATIONS SHALL NOT B	<u> </u>	
DESCRIPTION	MINIMUM REQUIREMENTS	BIDDER'S PROPOSAL MUST BE FILLED	
GENERAL			
Model	New, current production model compact track loader equivalent to Takeuchi TL10V ₂		
Cab Type	Enclosed Cab		
Operating Weight - Cab	10,270 lbs		
Tipping Load	7,205 lbs		
Bucket Breakout Force	6,520 lbs		
Lift Arm Breakout Force	5,400 lbs		
Traction Force	9,730 lbs		
Ground Pressure – Canopy	4.5 psi		
Travel Speed – Low	4.8 mph		
Travel Speed – High	7.0 mph		
HYDRAULIC SYSTEM			
Auxiliary Flow – Primary Circuit	18.8 gpm		
High Flow with Standard Secondary Circuit	32.8 gpm / 18.8 gpm (Aux Flow Secondary Circuit)		
Hydraulic System Pressure	3,481 psi		
ENGINE			
Туре	Diesel		
Fuel Tank Capacity	21.5 gal		
Horsepower	74.3 hp		
Maximum Torque	195ft-lb		
Engine Lubrication	11.8 qt		
Fuel Consumption (65% of full load)	2.7 gal/hr		
Hydraulic Reservoir Capacity	9.5 gals		
MACHINE DIMENSIO	ONS		
Maximum Lift Height to Bucket Pin	10 ft 4.8 in		
Dump Height Fully Raised	7 ft 11.9 in		
Dump Reach Fully Raised	3 ft 1.4 in		
Dump Angle	40 degrees		



DESCRIPTION	MINIMUM REQUIREMENTS	BIDDER'S PROPOSAL MUST BE FILLED	
MACHINE DIMENSIONS (CONT.)			
Rollback Angle	27 degrees		
Track Ground Contact Length	4 ft 7.9 in		
Machine Length	9 ft 7.2 in		
Transport Length	12 ft 1.0 in		
Transport Height	8 ft 0.0 in, maximum		
Clearance Circle with Bucket	8 ft 0.0 in, maximum		
Clearance Circle without Bucket	5 ft 0.0 in		
Clearance Circle Rear	5 ft 5.2 in		
Track Width	15.7 in		
Ground Clearance	11.0 in		
Overall Width without Bucket	5 ft 8.5 in		
FEATURES			
Operator Station	Polycarbonate Door and Top Guard		
Utility Brush Mower Attachment	Erskine Model 72" (P/N 901510), or approved equal Hydraulic Flow – 17-32 GPM		
	Operating Weight – 1,080 lb		
	Cutter Capacity – Material up to 3"		
	Deck Steel Thickness – 1/4"		
Hydraulic Equipment	Hydraulic Quick Coupler		
	Aux Flow – High Flow (32.8 GPM)		
	Rotating Beacon Light		
Bucket	4 in 1 bucket, 72" width, bolt on cutting edge		
MANUALS	The following manufacturer's manuals shall be provided: a) Operators manual b) Service manual c) Parts manual		
WARRANTY	Manufacturers Standard Warranty.		
NOTE	Unit shall be brand new and complete, meeting these specifications as well as the general catalog specifications describing this unit. Unit shall be completely assembled, serviced and in good running order and delivered to the destination indicated.		
DELIVERY	180 calendar days or sooner.		

